

# Datasheet

## NHS 150i Hydrodrive Easy Line

As a super flexible solution for chipping tasks in garden, park and places where accessibility is sometimes difficult, we have launched a full-hydraulic solution for mini loaders.

A very functional alternative to those who already have the mini loader with them on construction tasks.

The Hydro-Drive for EasyLine series is available in two sizes:

75ccm:

-To machines with oil supply from min. 75 to max. 100 l / min. and max. 350 bar pressure

52ccm:

-To machines with oil supply from min. 50 to max. 65 l / min. and max. 350 bar pressure



|   |               |
|---|---------------|
| Max. log diameter / (Opening) [mm]                            | 150 (150x170) |
| Required oil supply [l/min]                                   | 70-90         |
| Oil pressure [bar]  | 190-300       |
| Revolutions, Chipping disc [rpm]                              | (540)/1000    |
| Blades (hardened) [pcs.]                                      | 4             |
| Counter blades [pcs.]   | 1             |
| Cut per revolution  | 2             |
| Chipping disc diameter [mm] / weight [kg] (EasyCut)           | Ø600/60       |
| Hydraulic feedroller/feedrollers<br>[1 hydraulic, 1 follower] | √*            |
| Blade-adjustment (chip-size) [mm]                             | 7/15          |
| NHS InfoCon   | √             |
| Hourcounter / Service-planner                                 | √             |
| Chip-production per hour [m <sup>3</sup> ]                    | 8             |
| Opening, funnel - W/H [mm]                                    | 990/720       |
| Opening, Feedrollers - H/W [mm]                               | 150/170       |
| Discharge Pipe  | √             |
| Capacity, hydraulic oil tank [litr]                           | 20            |
| Overrunning clutch, hydraulics                                | √             |
| 3 pt. suspension category                                     | 1/2           |
| Length [mm]   | 2400          |
| Width [mm]  | 1170          |
| Height [mm]   | 2035          |
| Weight [kg.]  | 525           |
| Shipping dim. in meters [L/W/H]                               | 2,4/1,3/2,4   |
| Noise (workplace measurement) [dBA]                           | 104           |