

NHS 180i Standard Line

NHS 180 is the very DNA of NHS wood chippers. With over a decade in production, it is by far the most well-tested machine in the range.

The *i*-model is with integrated hydraulics (internal hydraulics)

It has an aggressive and precise intake, and delivers a nice and uniform chip quality. With a robust construction in a well-constructed geometry, you have a reliable machine that ensures an optimal working environment.

NHS 180 offers a wide selection of additional equipment.



| | |
|---|--------------|
| Max. Log diameter [mm] | 180 |
| Min./max. Power input [HP] | 35/100 |
| Revolutions PTO [rpm] | 540/ 1000 |
| Revolutions, Chipping Disc [rpm] | 540/ 1000 |
| Blades (hardened) [pcs.] | 4 |
| Counter blades [pcs.] | 2 |
| Cut per revolution [pcs.] | 2 |
| Chipping Disc diameter [mm] / Weight [kg] (EasyCut) | Ø710/135 |
| Hydraulic feedroller/feedrollers | √ |
| Capacity, hydraulic oil tank [litr] | 52 |
| Blade-adjustment (chip-size) [mm] | 8/14 |
| NHS InfoCon | √ |
| Hourcounter/ serviceplanner | √ |
| Chip-production per hour [m ³] | 15 |
| Opening, funnel - W/H [mm] | 1190/880 |
| Opening, feedrollers - H/W [mm] | 180/ 180 |
| Discharge Pipe | √ |
| Overrunning clutch | √ |
| Safety clutch, PTO-shaft | √ |
| 3 pt. suspension category | 2 |
| Length [mm] | 2380 |
| Width [mm] | 1500 |
| Height [mm] | 2700 |
| Weight [kg.] | 810 |
| Shipping dim. in meters [L/W/H] | 2,4/1,5/2,05 |
| Noise (workplace measurement) [dBA] | 104 |