

Datasheet

NHS 220ev Standard Line

NHS 220ev is a side-fed chipper (90° in relation to travel-direction), which is a great advantage for clearing along paths and roads. The woodchipper is modular with a hot-dip galvanized base frame.

It is equipped with tow bar (wagon-coupling) for light tipper wagon or equivalent.

(max. Ball pressure: 500kg / max. Pull: 2000 kg.)

The chipper is robust, flexible and has a superior feeding system, which makes it the perfect all-rounder.

NHS 220ev is for external hydraulics (oil supply from tractor)



Max. Log diameter [mm]	220
Min./max. Power input [HP]	54/130
Revolutions PTO [rpm]	1000
Revolutions, Chipping Disc [rpm]	1000
Blades (hardened) [pcs.] EasyCut®	4
Counter blades [pcs.]	2
Cut per revolution [pcs.]	2
Chipping Disc diameter [mm] / Weight [kg] EasyCut®	Ø826/187
Hydraulic feedroller/feedrollers	√
Liters per minute [min./max.]	32/80
Blade-adjustment (chip-size) [mm]	8/14
NHS InfoCon	√
Hourcounter/ serviceplanner	√
Chip-production per hour [m³]	20
Opening, funnel - W/H [mm]	1200/ 900
Opening, feedrollers - H/W [mm]	220/ 220
Discharge Pipe	√
Overrunning clutch	√
Safety clutch, PTO-shaft	√
3 pt. suspension category	2
Length [mm]	2020
Width [mm]	2300
Height [mm]	2600
Weight [kg.]	1245
Shipping dim. in meters [L/W/H]	2,1/2,3/2,2
Noise (workplace measurement) [dBA]	104