

Datasheet

NHS 300iv Standard Line

NHS 300iv is a side-fed chipper (90° in relation to travel-direction), which is a great advantage for clearing along paths and roads.

With vertical feed rollers and hinged feed box, the daily servicing of blades and Counter blades is exceptionally easy!

It is equipped with tow bar (wagon-coupling) for light tipper or equivalent.
(max. Ball pressure: 500kg / max. Pull: 2000 kg.)

NHS 300iv is with integrated hydraulics.



| | |
|--|-------------|
| Max. Log diameter [mm] | 300 |
| Min./max. Power input [HP] | 68/130 |
| Revolutions PTO [rpm] | 1000 |
| Revolutions, Chipping Disc [rpm] | 1000 |
| Blades (hardened) [pcs.] | 4 |
| Counter blades [pcs.] | 1 |
| Cut per revolution [pcs.] | 4 |
| Chipping Disc diameter [mm] / Weight [kg] | Ø960/225 |
| Hydraulic feedroller/feedrollers | √ |
| Capacity, hydraulic oil tank [ltr] | 45 |
| Blade-adjustment (chip-size) [mm] | 10-15 |
| NHS InfoCon | √ |
| Hourcounter/ serviceplanner | √ |
| Chip-production per hour [m ³] | 30 |
| Opening, funnel - W/H [mm] | 1170/ 800 |
| Opening, feedrollers - H/W [mm] | 300/ 300 |
| Discharge Pipe | √ |
| Overrunning clutch | √ |
| Safety clutch, PTO-shaft | √ |
| 3 pt. suspension category | 2 |
| Length [mm] | 2300 |
| Width [mm] | 1900 |
| Height [mm] | 3000 |
| Weight [kg.] | 1600 |
| Shipping dim. in meters [L/W/H] | 2,3/1,9/2,4 |
| Noise (workplace measurement) [dBA] | 105 |